



THE WORLD'S VALUE LEADER
A WORLD-CLASS STRAPPING MACHINE COMPANY





H-45L Helios Battery Powered Strapping Tool

DESCRIPTION

Helios H-45L is a battery powered strapping tool with superior features and performance. It is suitable for most of the strapping requirements in every application. Helios H-45L delivers the highest productivity and performance to meet the customer's packaging needs.

MAIN FEATURES

Easy Single Handheld Operation

• One single thumb pressing to operate the tool. Tensioning, sealing, and cutting are done at the push of the start button. It is the most user-friendly tool.



For All Kinds of Flat Packages

• Suitable for a wide range of vertical and horizontal strapping applications, including construction materials, pallet, wood/panel board, paper, etc.





Quick and Simple Adjustment

 Adjustable sealing time allows individual setting for different strap types and guarantees high sealing efficiency. Strap tension adjustment can be easily done by a simple turn of the dial. Appropriate tension ensures ideal load security.



Bosch Battery and Charger

 German Bosch high capacity battery provides up to 560 (for PP) and 300 (for PET) strapping cycles per charge. Rechargeable battery with long battery life up to 1000 charges.

Friction Weld Sealing

• The advanced friction weld sealing technology guarantees reliable joint and high sealing efficiency for both PP and PET strapping.







MORE FEATURES

High Speed

• One of the fastest tool on the market. In less than 3 seconds, the strap is tensioned, sealed, and cut.

Ergonomic and Rugged Design

 Provides maximum operator comfort and impact resistant. With little effort, packages such as boxes, pallets, bales, and crates can be safely strapped and secured during shipment and storage.

Easy Strap Threading

• Strap feeding is extremely simple. Both end of straps are inserted into the tool together. shipment and storage.

Flexible Tensioning Mode

 Automatic mode offers fast, one-button tensioning and sealing. Semi-auto mode offers flexibility to get specific tension. Both modes guarantee the loads are perfectly secured with the appropriately tensioned straps.

OPTIONS

- Suspension bracket
- Bottom base wearing protection plate







TECHNICAL DATA	Tension Range Strap Width	Up to 250 kg 9 mm (H-45L-09) 11 mm - 13 mm (H-45L-12) 15 mm - 16 mm (H-45L-16)
	Strap Thickness	PP : 0.55 - 1.05 mm PET : 0.5 - 1.05 mm
	Weight (incl. battery)	4.26 kg
	Battery	Bosch Li-lon 14.4V 4.0 Ah
	Battery Charger	Bosch 115V (110-120V), 230V (220V-240V) 50/60 Hz 1 PH



H-45L





- 17901 Von Karman Ave. Suite 600 Irvine, CA, 92614
- info@corrugatedboxequipment.com
- www.corrugatedboxequipment.com
- USA 949 242 9516 / 949 556 8744 MEX 55 7587 7681 / 55 8421 91591