







Kronos H-46 Battery Powered Tool for Plastic Strapping

DESCRIPTION

Kronos H-46 is a world-class battery powered strapping tool. With f lexible settings, wide tension range, and the ability to accommodate both PP and PET strapping, Kronos H-46 is ideal for a wide range applications in all industries and sectors. Kronos H-46 delivers the highest productivity and performance to meet the customers' packaging needs.

MAIN FEATURES

Easy Operation

• The operation of H-46 is extremely easy. Automatic mode offers fast one-button operation to complete the strapping process in less than 5 seconds. Versatile design with auto, semi-auto, manual, and soft modes satisfies various strapping requirements.



Digital Touch Panel

 Quick and easy setting through touch panel for various operation modes, tension force, and sealing time simplifies the operation. The digital readout on the panel also shows the battery power level, cycle counter, and error codes.







Wide Tension Force Range

 Easy tension adjustment on the digital touch panel. Variable tension force from 40 kg to 400 kg makes H-46 suitable for various applications in all industries and sectors like brick, wood, corrugated, paper, logistic, etc



Bosch Battery and Charger

 German Bosch high capacity battery provides up to 415 (for PP) and 320 (for PET) strapping cycles per charge on high tension mode. Rechargeable battery with long life span up to 1,000 charges.



Friction Weld Sealing

• The advanced friction weld sealing technology guarantees reliable joint and high seal efficiency for both PP and PET strapping. An automatic weld function speeds up cycle time.



MORE FEATURES

No Adjustment Required for Different Strap Thickness

•No adjustment is required for different strap thickness, and the cooling time will be automatically adjusted according to different tension.

Brushless Motor Technology

 German-made brushless DC motor direct drive technology provides the highest level of accuracy and reliability. The state-of-art technology results in less maintenance and longer life time of the motor.

Robust Housing

• The thick and solid structure provides outstanding impact resistance.

Perfect Balance and Ergonomic Design

• Ergonomic handle with anti-skid design and well-balanced structure make operation easy and effortless.

Energy Saving Mode

 Tool would automatically go to sleep mode if the tool sits idle for a while for energy saving purpose.

OPTIONS

- Suspension bracket
- Bottom base wearing protection plate
- Cover for tension and sealing switch to avoid dust







	Model Number	H-46A Light & Universal application	H-46B Heavy industry application
	Tension Range	40 - 250 kg	40 - 400 kg
	Strap Width	11 mm - 13 mm 15 mm - 16 mm	15 mm - 16 mm 19 mm
TECHNICAL DATA	Strap Thickness	PP : 0.6 - 1.05 mm PET : 0.5 - 1.05 mm	PP : 0.75 - 1.30 mm PET : 0.60 - 1.30 mm
	Net Weight	4.3 kg	4.4 kg
	Battery	Bosch Li-lon 18V, 4.0Ah	
	Battery Charger	Bosch 115V (110-120V), 230V (220V-240V) 50/60 Hz 1 PH	



H-46





- 17901 Von Karman Ave. Suite 600 Irvine, CA, 92614
- **⋈** info@corrugatedboxequipment.com
- www.corrugatedboxequipment.com
- USA 949 242 9516 / 949 556 8744 MEX 55 7587 7681 / 55 8421 91591