




FLEXO PRINTER SLOTTER

Model SYKM-H-1636-2ST



CHARACTERISTICS

- Lead edge feeder.
- Working speed 100-150 sheets/min.
- PLC control system.
- Motorized adjustment of each unit open/close and with alarm ringing.
- Each unit driven by a separate motor.
- All shafts pressure adjusted by motor.Gear system adopt spray lubrication.
- All shafts coated hard chromium.



SPECIFICATIONS

Flexo Printer Slotter Model SYKM-H-1636-2ST	
Machine design speed	180 sheet/min
Suitable working speed	100-150 sheet/min
Max. sheet size	1600 x 3600mm
Min. sheet size	500 x 760 mm
Max. printing area	1550 x 3400mm
Sheet Thickness	2 - 10 mm
Printing Die Thickness	5 - 7mm
Min. slotting space	160 x 160 x 160 x 160 or 300 x 60 x 300 x 60
Feeding Accuracy	+/- 1.0 mm
Printing Accuracy	+/- 0.5 mm
Slotting accuracy	+/- 1.5 mm



MODULES

Feeding Unit

- · Lead Edge Feeder
- Sheet Stop Adjustment
- Vaccum Dust Removing Devide
- · Feeding Roller
- Start Protection Device
- · Control Panel



Printing Unit

- •Anilox Roll Coated Hard Chromium, Line Screen 200-240 LPI
- •Ceramic Anilox Roll, Line Screen 300-450 LPI (OPTIONAL)
- Doctor Roll
- Pressure REgulation
- Printing Registration Regulation
- Registration Locking System
- Diaphragm Ink Pumps
- Control Panel



Die Cutting Unit

- •Anvil Cylinder Surface Coated Hard Chromium
- •Speed Differential Compensation Function
- •Anvil Cover Brand Maxdura, Dicar, CUE
- •Anvil Cover Repairing Device
- •Die Cutting cylinder Surface coated hard chromium
- •Regulation of die cutting cylinder registration
- •Pneumatic Lift Device
- •Independent Servo Motor Drive
- •Control Panel



Slotting Unit

- Pre-Creasing Wheel
- Creasing Wheel
- Slotting Blade Shaft
- · Slotting Blade / Trimming blade
- Regulation of Slotting Unit, is controlled by PLC and adjusted through touch screen
- Slotting Registration Regulation
- Control Panel



Stacker Unit

- Automatic and Manual Model
- Transmitting Belt
- Sheet Stacking Height 1600mm
- Sheet Collecting Table







- 17901 Von Karman Ave. Suite 600 Irvine, CA, 92614
- **™** info@corrugatedboxequipment.com
- www.corrugatedboxequipment.com
- USA 949 242 9516 / 949 556 8744 MEX 55 7587 7681 / 55 8421 91591